

FLOOR

SHIP TO

CUSTOMER

JOB NAME

REVISIONS ₽EV DESCRIPTION DATE ΒY IN-LINE OPP. STOPS: 2 OPENINGS: 2 Upper & Lower TRAVEL: TBD RATED LOAD: 125 Lb BI-PARTING DRYWALL CONSTRUCTION SWING MASONRY CONSTRUCTION FLOOR LOADING PLAIN STEEL - PRIMED HDISTWAY DOORS STAINLESS SILLS STAINLESS STEEL - #4 FUSIBLE LINK COUNTER LOADING 1 1/2 HR LL "B" LABEL EMERGENCY RELEASE NON-PLUGABLE INTERLOCK 🗡 HG-1 SINGLE CONTACT DOOR LOCK & CONTACT NEMA 1 HG-2 DOUBLE CONTACT INTERLOCK NEMA 1 JAMB MOUNTED 24V GEN-II KEYPAD WITH IN USE AND CAR HERE LIGHTS CAR PLAIN STEEL X STAINLESS STEEL - #4 GATE BI-PARTING COLLAPSIBLE SLIDE-UP ALUMINUM BY EII STAINLESS STEEL - #4 PLAIN STEEL ACCESS DOOR 1 1/2 HR U/L "B" NONE / BY OTHERS HOISTWAY TO BE BUILT BEFORE DUMBWAITER IS INSTALLED EXCEPT THE WALLS ARE TO BE DMITTED WHERE HOISTWAY DOORS OCCUR UNTIL THE DUMBWAITER IS INSTALLED & HOISTWAY DOORS ARE SET IN PLACE SPECIAL REQUIREMENTS DRIVE TYPE: WINDING DRUM RATED SPEED: 30 FPM CONTROLLER MODEL: INTELI-LIFT POWER: 115V 20 AMP

Elevation Innovation Inc

Compliant with all current ASME A17.1 & CSA B44 Codes

APPROVED

DATE

TITLE : Inteli-Lift 24 x 24 x 24 Front Back with Bi-Parting Gates

SHEET

1 DF 2

