

FLOOR

## REVISIONS ₽EV DESCRIPTION DATE ΒY STOPS: 2 IN-LINE OPP. TRAVEL: TBD RATED LOAD: 250 Lb BI-PARTING DRYWALL CONSTRUCTION SWING MASONRY CONSTRUCTION FLOOR LOADING PLAIN STEEL - PRIMED HDISTWAY DOORS STAINLESS SILLS STAINLESS STEEL - #4 FUSIBLE LINK COUNTER LOADING 1 1/2 HR LL "B" LABEL EMERGENCY RELEASE NON-PLUGABLE INTERLOCK 🗡 HG-1 SINGLE CONTACT DOOR LOCK & CONTACT NEMA 1 HG-2 DOUBLE CONTACT INTERLOCK NEMA 1 JAMB MOUNTED 24V GEN-II KEYPAD WITH IN USE AND CAR HERE LIGHTS CAR PLAIN STEEL XI STAINLESS STEEL - #4 GATE BI-PARTING COLLAPSIBLE SLIDE-UP ALUMINUM BY EII STAINLESS STEEL - #4 PLAIN STEEL ACCESS DOOR 📈 1 1/2 нR U/L "В" NONE / BY OTHERS HOISTWAY TO BE BUILT BEFORE DUMBWAITER IS INSTALLED EXCEPT THE WALLS ARE TO BE OMITTED WHERE HOISTWAY DOORS OCCUR UNTIL THE DUMBWAITER IS INSTALLED & HOISTWAY DOORS ARE SET IN PLACE SPECIAL REQUIREMENTS DRIVE TYPE: WINDING DRUM RATED SPEED: 30 FPM CONTROLLER MODEL: INTELI-LIFT POWER: 115V 20 AMP

## Compliant with all current ASME A17.1 & CSA B44 Codes

CUSTOMER	JOB NAME	SHIP TO	TITLE : Inteli-Lift 30 x 30 x 36 Front Back with Bi-Parting Gates					
			APPROVED					
	DATE		DATE	SHEET	1 DF 2		Elevation Innov	ation Inc

