



Elevation Innovation Inc.
6060Enterprise Dr Suite A
Diamond Springs, CA 95619
Phone: 530-295-4900
Fax: 877-285-3050

Econo-Lift® 150 Dumbwaiter Specifications

DEFLECTION	150# dumbwaiter will carry 150 lbs and meet all codes per ANSI for cab deflection.
DESIGN	Floor loading or Counter height
CAR	24"x24"x30" or Custom Size and Shape
SIZE	Up to 6.9 ft cubed
MATERIAL	9 Ply birch, steel or Stainless Steel
OPENING	One, two or three sides available.
CAPACITY	150 lbs
SPEED	30 fpm
POWER	115v 20 AMP
POWER UNIT	Underneath, or overhead.
WINDING DRUM	High torque electric motor and completely enclosed worm gear, drums threaded to accommodate a single 1/8" x 7 x 19 improved plow stainless steel cable.
GUIDE RAIL	Monorail type
CONTROLS	Fully automatic allowing car to be sent or called from any floor. Terminal limit switch provided for finals. Car stops automatically at landing levels. Door interlocks for hoistway doors to prevent operation of the dumbwaiter unless doors are closed and to prevent opening of any door except when the car is at the landing.
CONTROLLER	16" wide x 16" tall x 6" deep
ETL File# 5020834	Fully ETL Certified to: USA - ASME A17.1 & A17.5 / Canada CSA B44
OPTIONAL EQUIPMENT	Roll top gate, removable adjustable shelves, 3" retaining lip on opening.